

Energy Efficient Side Mounted Undercounter / Benchtop Refrigerators



LTR920



LTR1271



LTR1571



LTR1871

Features and Benefits

Stainless Steel Construction

The interior is 304 grade with coved floors. The exterior is 430 grade (except galvanized steel rear and base.)

Foamed in place insulation using high density polyurethane close cell. CFC free.

Design

All units exclusively have contoured lines, rounded corners and recessed door handles for a modern, elegant look. All units have adjustable vinyl coated wire shelves with unique durable plastic shelf clips.

Efficient Refrigeration System

The Lassele LTR range of refrigerators are forced draft and frost free.

Operating temperature (Rating at 38 °C ambient)

-Fridge: -2°C to 4°C

Other Standard Features

- Electronic temperature controller.
- Facia heater for condensation free convenience.
- Self closing doors.
- 100 mm castors for under counter location.

Options

- Glass doors.
- 304 grade worktop.
- 155 mm (2 lockable.) for bench top application.



MODEL	UNIT TYPE	PACKED WEIGHT	DOORS	LITRES	METRIC (mm) W x D x H*	VOLTS	AMPS	REFRIGERANT	SHELVES
LTR920	FRIDGE	53kg	1	210ltr	920 x 700 x 740	220-240	3.0	R134A	1 ROW
LTR1271	FRIDGE	78kg	2	300ltr	1200 x 700 x 740	220-240	3.0	R134A	1 ROW
LTR1571	FRIDGE	89kg	2	412ltr	1500 x 700 x 740	220-240	3.5	R134A	1 ROW
LTR1871	FRIDGE	107kg	3	521ltr	1800 x 700 x 740	220-240	4.0	R134A	1 ROW

*Plus castor options