



Energy Efficient Top Mounted Dual Temp Cabinets



LRF1382/ LRF1383



LRF1382 -1G



LS1660RF



Features and Benefits

Stainless Steel Construction

The interior is 304 grade with covered floors. The exterior is 430 grade (except galvanized steel rear, top and base.) Foamed in place insulation using high density polyurethane close cell. CFC free.

Design

All units exclusively have contoured lines, rounded corners and recessed door handles for a modern, elegant look. All units have adjustable vinyl coated wire shelves with unique durable plastic shelf clips.

Efficient Refrigeration System

The Lassele solid refrigerators and freezers are designed with oversized evaporators and condensers for fast cooling and greater efficiency. Forced draft, frost free. (Electric defrost system on freezers.) Bottom mounted condensing set for easy service access. This also allows the cabinet product loading to be at an ergonomically correct level. Operating temperature (Rating at 38 C. ambient)
 -Fridge: -2°C to 4°C
 -Freezer: -18°C to -22°C

Other Standard Features

- Electronic temperature controller.
- Facia heater for condensation free convenience.
- Self closing doors.
- Internal light operated by door switch.
- Automatic evaporator fan delay when door open.
- 150 mm castors (2 lockable.)

Options

- Door locks.
- Glass insert doors.

MODEL	UNIT TYPE	PACKED WEIGHT	DOORS	LITRES	METRIC (mm) W x D x H	VOLTS	AMPS	REFRIGERANT	SHELVES
LRF1382HRFS	½ R / ½ F	210kg	4 x ½ doors	500R/ 500F ltr	1260x 810x 1865	220-240	2 x 3.5	R134A / R404A	6
LRF1382HRFS-1G	½ R / ½ F	220kg	4 x ½ doors 1 x glass	500R/ 500F ltr	1260x 810x 1865	220-240	2 x 3.5	R134A / R404A	6
LRF1383RFS	¾ R / ¼ F	215kg	4 x ½ doors	750R/ 250F ltr	1260x 810x 1865	220-240	2 x 3.5	R134A / R404A	6
LS1660RF	2/3R / 1/3F	310kg	6 x ½ doors	1000R/ 500F ltr	1900x 810x 1865	220-240	1 x 4 1 x 3.5	R134A / R404A	9
LS1660RF-2G	2/3R / 1/3F	300kg	6 x ½ doors 2 x glass	1000R/ 500F ltr	1900x 810x 1865	220-240	1 x 4 1 x 3.5	R134A / R404A	9