



## Energy Efficient Reach-in Refrigerators and Freezers



**LRB771 / LFB771**



**LRB1471 / LFB1471**

### Features and Benefits

#### Stainless Steel Construction

The interior is 304 grade with coved floors.  
The exterior is 430 grade (except galvanized steel rear, top and base.)  
Foamed in place insulation using high density polyurethane close cell. CFC free.

#### Design

All units exclusively have contoured lines, rounded corners and recessed door handles for a modern, elegant look. All units have adjustable vinyl coated wire shelves with unique durable plastic shelf clips.

#### Efficient Refrigeration System

The Lassele solid refrigerators and freezers are designed with oversized evaporators and condensers for fast cooling and greater efficiency. Forced draft, frost free. (Electric defrost system on freezers.)

Bottom mounted condensing set for easy service access. This also allows the cabinet product loading to be at an ergonomically correct level.

Operating temperature (Rating at 38 C. ambient)

-Fridge: -2°C to 4°C

-Freezer: -18°C to -22°C

#### Other Standard Features

- Electronic temperature controller.
- Facia heater for condensation free convenience.
- Self closing doors.
- Internal light operated by door switch.
- Automatic evaporator fan delay when door open.
- Door locks.
- 100 mm castors (2 lockable.)



MODEL	UNIT TYPE	PACKED WEIGHT	DOORS	LITRES	METRIC (mm) W x D x H	VOLTS	AMPS	REFRIGERANT	SHELVES
LRB771	FRIDGE	130kg	1	580 ltr	680x 790x 2100	220-240	3.5	R134A	4
LRB1471	FRIDGE	210kg	2	1265 ltr	1370x 790x 2100	220-240	4.0	R134A	8
LFB771	FREEZER	130kg	1	580 ltr	680x 790x 2100	220-240	4.5	R404A	4
LFB1471	FREEZER	210kg	2	1265 ltr	1370x 790x 2100	220-240	5.5	R404A	8